



## Pakknippel Polyamid IP66/68 Ex i Metrisk

Ex-i for upansret kabel

### Spesifikasjon

MATERIALE	Polyamid
PAKNING	EPDM
TÄTNINGSRING	EPDM
BESKYTTELSESGRAD	IP66, IP68 - 5 bar (30 min.)
TEMPERATUROMRÅDE	-40°C...+75°C (M12 +15°C...+65°C)
FARGE	Blå RAL 5012/Sort RAL 9005
KATEGORI / ZON	2 G (1,2) 2 D (21,22)
UTRUSTNINGSGRUPP	II
TYPE AV BESKYTTELSE	Ex eb, Ex tb
CERTIFIKAT	IECEX, ATEX

## Varianter

ARTIKKELNR	YTTERGJENGE	FOR KABEL Ø MM	L MM	H MM	SW MM	E MM	ANTALL/PKN
ESKE/1-1 12	M12x1,5	3 - 6	9	37	16	18	50
ESKE/1-1 16	M16x1,5	4,5 - 9	9	37	20	22	50
ESKE/1-1 20	M20x1,5	7 - 13	10	45	24	27	50
ESKE/1-1 25	M25x1,5	10 - 17	10	47	29	32	50
ESKE/1-1 32	M32x1,5	13 - 21	12	51	36	40	25
ESKE/1-1 40	M40x1,5	17 - 28	12	65	46	51	10
ESKE/1-1 50	M50x1,5	23 - 35	14	72	55	61	4
ESKE/1-1 63	M63x1,5	34 - 48	15	78	68	75	1