



Blindplugg Polyamid IP54 RAL 7035 PG

Spesifikasjon

| | |
|-------------------------|-------------------------------------|
| MATERIALE | Polyamid 6 GF30 Glasfiberforsterket |
| BESKYTTELSESGRAD | IP54 |
| TEMPERATUROMRÅDE | -40°C...+100°C |
| FARGE | Lysgrå RAL7035 |
| HALOGENFRI | Ja |

Varianter

| EL-NUMMER | YTTERGJENGE | L MM | DA MM | H MM | ANTALL/PKN |
|-----------|-------------|------|-------|------|------------|
| 1007PA | PG7/12,5 | 6 | 15 | 10 | 100 |
| 1009PA | PG9/15,2 | 6 | 19 | 10 | 100 |
| 1011PA | PG11/18,6 | 6 | 22 | 10 | 100 |
| 1013PA | PG13,5/20,4 | 6 | 25 | 10 | 100 |
| 1016PA | PG16/22,5 | 6 | 27 | 10 | 100 |
| 1021PA | PG21/28,3 | 8 | 33 | 12,5 | 100 |
| 1029PA | PG29/37,0 | 8 | 44,5 | 13 | 100 |
| 1036PA | PG36/47,0 | 10 | 55,5 | 15 | 50 |
| 1042PA | PG42/54,0 | 10 | 62,5 | 15,5 | 50 |
| 1048PA | PG48/59,3 | 12 | 69,5 | 17 | 50 |

